

PRINTDOT

B9 SERIES

CUTTING INDUSTRY
INTEGRATED SOLUTIONS



Equipo: B9

PrintDot

Put your business in the hands of someone who knows

Product Specifications

Model No.	B9			
Model No	B9-1013	B9-1815	B9-2516	B9-3020
Effective Cutting Area(MM)	1000X1300	1800X1500	2500X1600	3000X2000
Special Size	Customizable			
Safe Device	Physical anti-collision mechanism + infrared induction anti-collision to ensure productionsafety			
Tools	• Electric oscillating tool, Universal cut tool, Kiss cut tool, CCD, Cursor, Pen • Pneumatic oscillating tool, Power rotary tool, Creasing tool, VCUT, Universal router tool			
Cutting Thickness	≤ 50mm			
Cutting Speed	≤ 2500mm/s			
Cutting Precision	≤ 0.1mm			
Repeated Accuracy	≤ 0.05mm			
Fixing Method	Vacuum suction			
Interface	Ethernet port			
Driving System	Intelligent digital control servo system			
Command	DXF, HPGL, PDF, PLT compatible format			
Control Panel	Multi-language LCD touch panel			
Overall Dimension(MMM)	2050*2250*1260	2850*2450*1260	3350*2550*1260	4050*2950*1265
Machine Weight(KG)	550	730	900	1150
Suction Power	3KW	7.5KW	7.5KW	11KW
Power Supply	AC220/380V 50~60Hz			
Working Environment	Temperature: -10°C~40°C, Humidity: 20%~80%RH			
Upgradeable Configuration	•Vacuum pump with frequency transformer •Aluminum vacuum table with 8 air zones •Vacuum pump silencing box •Rack transmission			