

PRINTDOT DTF-700

Specification



Machine Tyoe	DTF- 700					
Print Head	2H			4H		
Print Mode		360/1800 3p	360/2400 4p		360/1800 3p	360/2400 4p
Speed with 8 heads		25sqm/h	20sqm/h		50sqm/h	40sqm/h
Print Width	650MM					
Printer Interface	NET WORK					
Media Transmission	Roll to Roll					
Data Transfer	Edge RIP while print / RIP post-print					
RIP Software	PHOTOPRINT,MAINTOP					
Drying System	Infrared drying and fan-air dry					
Cleaning System	Separation dual function of pressure and suction cleaning					
Material Systems	belt conyor , airshaft system					
Ink Types	C,M,Y,K, LC, LM , W, V					
Power Requirements	220 VAC ,<16A, 50/60HZ					
Working Environment	Temperature:23°C ~28°C , Humidity:45%~55%RH					
Media Type	DTF FILM, DTP PAPER					
Dimensions	3500*1030*1570 mm(L*W*H)					
NW/GW						



浙江普印科技有限公司

地址:浙江省嘉兴市秀洲区加创路1509号12号厂房
Add:BLD 12 , No1509 , Jiachuang Road , Xiuzhou district,
Jiaxing city , Zhejiang province , China

Panasonic
INDUSTRY

NSK
MOTION & CONTROL

fa
tech

igus