

PRINTDOT

PY1908

Specification



Machine Tyoe	A1/E1 Digital Inkjet Printer PY1908				
Print Head	8H				
Print Mode	360/1200 1p	360/1800 3p		360/2400 4p	
Speed with 8 heads	340sqm/h	230sqm/h		120sqm/h	
Print Width	1.9M (printing table 2.05meters)				
Printer Interface	GB NET WORK				
Media Transmission	Roll to Roll				
Data Transfer	Edge RIP while print / RIP post-print				
RIP Software	PHOTOPRINT,MAINTOP,NEOSTAMPA, WASATCH				
Heating System	Four-heating:Before printing,printing,printing post,Ink heating				
Drying System	Infrared drying and fan-air dry				
Cleaning System	Separation dual function of pressure and suction cleaning				
Material Systems	Normal double motor rewinder / swing roller tension rewinder / airshaft system,				
Ink Types	C,M,Y,K, LC, LM , O, R , G , B, fluorescent color				
Power Requirements	220 VAC ,<4A, 50/60HZ + heater 220 VAC ,<50A,50/60HZ				
Working Environment	Temperature:23°C ~28°C , Humidity:45%~55%RH				
Media Type	flex banner , vinyl , non-wooden cloth, wall paper , pp paper , sublimation paper				
Dimensions	3300*1030*1570 mm(L*W*H)				
NW/GW	850KG/1000KG				
Quality parts	German Igus drag chain	German Igus Power cable	Italy Elateck belt	Full aluminum beam	Standard nagetive pressure
	Japan THK guide rail	Japan NSK bearing	Japan Omron sesors	Smart pinch roller	Smart hot wind drying high efficient



浙江普印科技有限公司

地址:浙江省嘉兴市秀洲区加创路1509号12号厂房
Add:BLD 12 , No1509 , Jiachuang Road , Xiuzhou district,
Jiaxing city , Zhejiang province , China

Panasonic
INDUSTRY

NSK
MOTION & CONTROL

tech

igus