

PY3204UV


High Speed with four I3200-U1 heads



UV Solvent Ink



Four I3200-U1 Heads



* 3.2m Four I3200-U1 Print Heads Speed

360x2400dpi - 4pass	50 m ² /h
720x1800dpi - 6pass	35 m ² /h
720x2400dpi - 8pass	23 m ² /h

Equipo UV



APPLICATIONS : lightbox, transparent film, car sticker, wallpaper, silk canvas and other advertising decoration materials

PrintDot

Put your business in the hands of someone who knows

• Technical Specifications

Model	PY3204UV
Print Head	Four I3200-U1 Print Heads
Printing Technology	Piezoelectric Inkjet
Width	126.7 in.(3220 mm)
Acceptable Media Thickness	Maximum 39.3 mil(1 mm)
Weight	176 lb.(80 kg)
Printing Width	125.9 in.(3200 mm)
Ink Cartridges Type	UV Ink
Capacity	4*4 CISS (220ml ink cartridge with 3L ink tank)
Color	CMYK/CMYK+W/CMYK+W+CMYK/CMYKLCLM
Printing Resolution	Maximum 2400 dpi
Printing Speed	Frontlit mode : 4pass(360x2400dpi) : 50 sqm/h Frontlit mode : 6pass(720x1800dpi) : 35 sqm/h Frontlit mode : 8pass(720x2400dpi) : 23 sqm/h
Ink Curing Unit	Dual UV LED Lamps
Interface	Network
Power Supply	AC 220V ± 10%, 50/60 HZ
Dimensions(with stand)	181.8(W)x38.1(D)x61.4(H) in. (4620(W)x970(D)x1560(H) mm)
Weight(with stand)	1543 lb. (700 kg)
Package Dimensions	Entirety Packing : 188.9(W)x43.3(D)x65.3(H) in. (4800(W)x1100(D)x1660(H) mm)
Package Weight	Entirety Packing : 1763.3 lb. (800 kg)
Environment	Power on Temperature: 59 °F to 90 °F [15°C to 32°C] (68 °F[20°C] / Humidity: 35 to 80% (no condensation) Power off Temperature: 41 °F to 104 °F [5°C to 40°C] / Humidity: 20 to 80% (no condensation)
Accessories	Stand, media loading and take-up system, bulk ink cartridge system, etc