

PRINTDOT

PY6003

Specification



Machine Model	PY6003			
Print Head	3H WCV			
Print Mode	360/2400 4p	360/3600 6p		
Speed	10sqm/h	7sqm/h		
Print Width	0.6M			
Printer Interface	GB NET WORK			
Media Transmission	Roll to Roll			
Data Transfer	Edge RIP while print / RIP post-print			
RIP Software	PHOTOPRINT,MAINTOP,NEOSTAMPA, WASATCH			
Heating System	Damper heating			
Drying System	UV water cooling lamp			
Cleaning System	Separation dual function of pressure and suction cleaning			
Material Systems	motor rewinder/ airshaft system,			
Ink Types	C,M,Y,K, LC, LM, O, R, G, B, White, Vanish, fluorescent color			
Power Requirements	220 VAC, <4A, 50/60HZ + heater 220 VAC, <50A, 50/60HZ			
Working Environment	Temperature:23°C ~28°C, Humidity:45%~55%RH			
Media Type	uvdtf film			
Dimensions	2102x860x1550 mm ³ (L*W*H) woodcase 2224x1120x800mm ³			
NW/GW	275KG/343KG			
Quality parts	German Igus drag chain	German Igus Power cable	Italy Elateck belt	Full aluminum beam
	Japan THK guide rail	Japan NSK bearing	Japan Omron sesors	Smart pinch roller



浙江普印科技有限公司

地址:浙江省嘉兴市秀洲区加创路1509号12号厂房
Add:BLD 12, No1509, Jiachuang Road, Xiuzhou district,
Jiaxing city, Zhejiang province, China

