

PRINTDOT

PY9060

Specification



Machine Model	PY9060			
Print Head	3/4H WCV			
Print Mode	360/2400 4p	360/3600 6p		
Speed	4.8sqm/h	6.5sqm/h		
Print Width	0.9M*0.6M			
Printer Interface	GB NET WORK			
Media Transmission	Flat bed			
Data Transfer	Edge RIP while print / RIP post-print			
RIP Software	PHOTOPRINT,MAINTOP,NEOSTAMPA, WASATCH			
Heating System	Damper heating			
Drying System	UV water cooling lamp			
Cleaning System	Separation dual function of pressure and suction cleaning			
Material Systems	Max 15cm height ,			
Ink Types	C,M,Y,K, LC, LM , O, R , G , B, White , Vanish ,fluorescent color			
Power Requirements	220 VAC ,<4A, 50/60HZ + heater 220 VAC ,<50A,50/60HZ			
Working Environment	Temperature:23°C ~28°C , Humidity:45%~55%RH			
Media Type	Rigid printing, sheet printing , Cylinderial printing			
Dimensions	1440x2030x1300 mm ³ (L*W*H) woodcase 2200x1530x1000mm ³			
NW/GW	307KG/410KG			
Quality parts	German Igus drag chain	German Igus Power cable	Italy Elateck belt	Full aluminum beam
	Japan THK guide rail	Japan NSK bearing	Japan Omron sesors	Smart pinch roller



浙江普印科技有限公司

地址:浙江省嘉兴市秀洲区加创路1509号12号厂房
Add:BLD 12 , No1509 , Jiachuang Road , Xiuzhou district,
Jiaxing city , Zhejiang province , China

