



| 参数parameters   |                                                                      |                                                                       |                                                                                              |
|----------------|----------------------------------------------------------------------|-----------------------------------------------------------------------|----------------------------------------------------------------------------------------------|
| 型号Model        | EP18/EP19                                                            | 双头/三头/四头/六头/八头 2H/3H/4H/6H/8H                                         |                                                                                              |
| 打印喷头Print-Head | I3200-A1                                                             |                                                                       |                                                                                              |
| 打印速度Speed      | EP18 双头 (2H)                                                         | EP18三头 (3H)                                                           | EP19 八头 (8H)                                                                                 |
|                | 3P 56m <sup>2</sup> /h 4P 40m <sup>2</sup> /h 6P 28m <sup>2</sup> /h | 3P 85m <sup>2</sup> /h 4P 70m <sup>2</sup> /h 6P 38m <sup>2</sup> /h  | 1P 320m <sup>2</sup> /h 2P 160m <sup>2</sup> /h                                              |
|                | EP19 双头 (2H)                                                         | EP19三头 (3H)                                                           | EP19四头 (4H)                                                                                  |
|                | 3P 57m <sup>2</sup> /h 4P 41m <sup>2</sup> /h 6P 29m <sup>2</sup> /h | 3P 85m <sup>2</sup> /h 4P 70m <sup>2</sup> /h 6P 39m <sup>2</sup> /h  | 4P 86m <sup>2</sup> /h 6P 57m <sup>2</sup> /h                                                |
| 打印宽幅:          | EP18: 1820mm                                                         | EP19: 1940mm                                                          |                                                                                              |
| 配置:            | Large Aluminum Beam 2940mm<br>高精密铝梁2940mm                            | Ultraprint/Maintop,<br>Photoprint/Onyx (Optional)<br>瑞彩/蒙泰, PP/ONYX选配 | THK/HIWIN quiet high precision<br>guid rail with Doulbe guid<br>block<br>日本THK/台湾上银 超静音双滑块导轨 |
|                | Germany LGUS Drag Chain<br>德国易格斯静音高性能拖链                              | Germany LCUS Power cable<br>德国易格斯耐弯折高柔线                               | Omrns original sensors package<br>日本欧姆龙高性能传感器组                                               |
|                | Ltaly ELATECH quiet Belt<br>意大利伊拉泰静音内钢丝皮带                            |                                                                       |                                                                                              |
| Features/设备概览  | 1.Heavy-Duty Deluxe extended<br>frame;<br>高性能重型机身                    | 2.High Mechanical Strength and<br>precision;<br>高强度结合高精度打印            | 3.The standard infrared<br>heating;<br>标配红外干燥                                                |

# PrintDot

Put your business in the hannds of someone who knows

## Equipo Sublimación

## Modelos: EP18 Y EP19